



AMAR TEX CHEM

COMPANY HAS BEEN IN THE TEXTILE CHEMICAL BUSINESS SINCE 2002

ANTISTATIC AGENT FOR ACRYLIC, RECYCLED & PET FIBRES AND THEIR BLEND

Antistat ECO LV 100

Antistat ECO LV 100 is oil processed product. It is eco-friendly It is Export & ZDHC certified product. it is a special blend of Petrochemical lubricants & antistatic agents.

The product is highly effective to form antistatic layer on fiber to increase smoothness and provide good spinning actions.

Typical Chemical & Physical Properties:

- | | | |
|----|-------------------|-----------------------------------|
| 1. | Appearance | Yellow brown liquid (Transparent) |
| 2. | Specific Gravity | App. 0.9-0.92 at NTP |
| 3. | Solubility | Freely soluble in water |
| 4. | Ph of 5% solution | 7.0 |

Application:

Antistat ECO LV 100 mix with binding agent (**Binder 5290**) applied for spinning of Acrylic 100% & Polyester 100% in ring frame and open-end spinning system.

Dosage:

The recommended dosage level		
Type of fibre	% ECO LV 100 O.W.	% Binder 5290 O.W. F
Dry spun Acrylic (100%)	0.3 to 0.35	0.1 to 0.15
Wet spun Acrylic (100%)	0.2 to 0.25	0.5 to 0.1
Dyed Recycled Polyester (100%)	0.2 to 0.25	0.1 to 0.15
Grey Recycled Polyester (100%)	0.1 to 0.15	0.05 to 0.1

(0.1 refer to approx. 1 Ltr in 1 ton material mixing)

(0.05 refer to approx. 500 grams in 1 ton material mixing)

Email Id: amartex_chem@yahoo.co.in,
Amartexchem0233@gmail.com

Contact Person: V.K. SONI
(94160-18727)